(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 15 January 2004 (15.01.2004)

PCT

(10) International Publication Number WO 2004/005877 A1

(51) International Patent Classification7: G01M 1/00

(21) International Application Number:

PCT/EP2003/007048

(22) International Filing Date: 2 July 2003 (02.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: TO2002A000585

5 July 2002 (05.07.2002) IT

(71) Applicant (for all designated States except US): TELE-COM ITALIA S.p.A [IT/IT]; Piazza degli Affari, 2, I-20123 Milano (IT).


(72) Inventors; and

(75) Inventors/Applicants (for US only): CAPONI, Renato [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). POTENZA, Marcello [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). ROCCATO, Diego [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). SCHIANO, Marco [IT/IT]; TELECOM ITALIA S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT).

- (74) Agents: GIANNESI, Pier, Giovanni et al.; Pirelli S.p.A., Viale Sarca 222, I-20126 Milano (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD, SYSTEM AND DEVICE FOR MEASURING THE POLARISATION MODE DISPERSION OF AN OPTICAL FIBRE



(57) Abstract: The present invention relates to a new model for interpreting interferometric measurements, able to lead to a new method, system (10) and device (27) for measuring the PMD (Polarisation Mode Dispersion) of an optical fibre (11). The model, which is based on the theory of propagation of the optical signal as can be determined according to the socalled Principal States of Polarisation (PSPs) of the fibre, leads to a new interpretation of the interferogram generated with the interferometric measurements and is characterised in that it identifies in said interferogram a central peak and two side lobes. Thanks to this new model, it is possible to determine the PMD of the fibre based on the information content associated to at least one of the two side lobes identified in the interferogram.



2004/005877 A1